



Durable, Safe, Economic, Convenient and with Excellent Ergonomics.

We satisfy the customer's unique demand and requirement!

[Excavator Mounted Flail Mower] New product, from WOOSUNG, the hallmark of advancement

over many years of research and development!



Woosung's EF Series excavator mounted flail mowers are designed to mo w grasses and cut twigs, where grow on inaccessible places to conventional tractors like steep slope, river banks / dikes, meadow and hilly areas.

Model for Mini Excavator



<EF600>

Model for Small Excavator



<EF800/EF1100/EF1300>

PATENTAPPLICATION NUMBER: 10-2015-0147077







Key Features





- Hydraulic Connection
 - : Hookup is simple and hoses connect directly to the hydraulic
- Frame Structure
- : Light-weight but highly rigid



: Compact-sized but come in excellent wear resistance and optimized to cut grasses, weeds, and small twigs.

Protection Valve

- : Diverts sudden build-up of pressure to the hydraulic motor and ensures to protect the hydraulic motor.
- Mechanical Float Adaptor
 - : This feature allows smooth mowing operation through the contour of the ground.







Specifications

100	1	
•	\mathbf{A}	
Cup knife type	3 Knife type	Hammer type

Model	EF600	EF800	EF1100	EF1300
Cutting Width	600mm 23.6in	800mm 31.5in	1100mm 43.3in	1300mm 51.3in
Flow	30~40 L/min 7.9~10.6 gal/min	50~70 min 13.2~18.5 gal/min		
Rated Pressure	245 kgf/cm2			
Number of	ber or Cup Krille	3 Knife type : 18set	3 Knife type : 26set	3 Knife type : 22ea
Knives		Hammer : 18ea	Hammer : 26ea	5 mile type : 22ea
Direction of Rotation	Unidirectional			
Weight	85kg 187lbs	170kg 375lbs	230kg 570lbs	550kg 1,190lbs
Applicable Excavator	1.7~2.5ton 3,3748~5,512 lbs	3~4.5ton 6,614~9,921 lbs	5~8ton 11,023~17,637 lbs	10~14ton 28,660~33,069 lbs





Types of Mount and Dimensions Tuno Dimen Milmon Limen

туре	D(mm)	w(mm)	L(mm)
Α	25	100	92
В	30	125	125
D	35	150	180
E	40	145	190
G	45	174	271
н	65	280	400

X Specifications subject to change without advance notice. Woosung Precision Industrial Co., Ltd





Durable, Safe, Economic,

Convenient and with Excellent Ergonomics.

We satisfy the customer's unique demand and requirement!

[Forestry Mulcher] New product, from WOOSUNG, the hallmark of advancement


over many years of research and development!



Woosung Forestry Mulcher can be installed on most excavator that the high performance hydraulic motor enables to cut brushes in fast speed and work on trees very efficiently!

Forestry Mulcher





<Forestry Knife>

<FM800>







Key Features





Hydraulic Connection
 : Hookup is simple and hoses connect directly to the hydraulic

motor.

Power Unit
: Equipped with a very powerful


hydraulic piston motor.

- Comes with knives of excellent cutting performance and wear resistance.
- Protection Valve
 - : Diverts sudden build-up of pressure to the hydraulic motor and ensures to protect the hydraulic motor.
- A tilting device enables to tackle the cut ting objects more efficiently!

Specifications









Types of Mount and Dimensions

Types	D(mm)	W(mm)	L(mm)
н	65	280	400

Specifications subject to change without advance notice.Woosung Precision Industrial Co., Ltd





Durable, Safe, Economic,

Convenient and with Excellent Ergonomics.

We satisfy the customer's unique demand and requirement!

[Excavator Mounted Trimmer] New product, from WOOSUNG, the hallmark of advancement

over many years of research and development!



Woosung Forestry Trimmer can be installed on most excavator that the high performance hydraulic motor enables to cut brushes in fast speed and work on trees very efficiently!

TRIMMER



<ET1500>







Key Features






- The trimmer body part rotates 360 degrees to be able to work
- Frame Structure
 : Light-weight but highly rigid design.

- The operation is based on a rotating cam
- Comes with knives of excellent cutting performance and wear resistance.



Specifications

Model	ET 1500	
Cutting Width	1500mm / 60in	
Motor	HYD motor 40~80cc	
Number of Knives	Knife 21ea	
Direction of Rotation	One-way	
Weight	250kg / 511lbs	
Applicable Excavator	3~4.5ton 6,614~9,921 lbs	





Types of Mount and Dimensions				
Туре	D(mm)	W(mm)	L(mm)	
G	45	174	271	

Specifications subject to change without advance notice.

— Woosung Precision Industrial Co., Ltd